



# UNITECHS' MINI-ROLL COMPACTOR



YOUR DRY GRANULATION EXPERT



### TECHNOLOGICAL BENEFITS

- o New feeding system guarantees a constant powder feed per batch.
- Validated force and gap measurement.
- o Constant product quality and properties
- Reduced parts for rapid changeover and cleaning procedures.
- o Convenient placement within the laboratory.
- Easy scale-up to production batches.
- o Ideal for pharmaceutical, food and chemical laboratories.

## > UTILITY

- Electrical Power 230 VAC, 50 Hz, 1 Phase+N+E
- O Power consumption 2 Kw
- O Charging height :- 1390mm
- O Discharging height: 710mm
- O Dimension :- 700 L x 830 W x 1590 H

### **UNITECH's Mini Roll compactor**

# **TECHNICAL SPECIFICATIONS**

FEATURE	DETAILS
ROLL SIZE	Ø60 mm x 25mm WIDTH
OUT PUT	0.3 TO 3 Kg/hour [Approx] Depending of powder & required Hardness.
ROLLER SURFACE	Plain / Corrugated / Knurled / Cross knurled As per Customer Requirement.
Gap between rolls	0.3 to 4mm +/- 0.2 [settable thru manual revolving Handle]
Roll speed range	2 to 18 RPM
Feed screw speed	10 to 100 RPM
Oscillation granulation speed	1 to 100 RPM
Feed Hopper capacity	0.5 Litre Approx
PLC	Available
HMI	Available

=FASTER / SMARTER / RELIABLE

=THE FASTEST WAY FROM THE

IDEA TO THE MARKET.

### **UNITECH MACHINERIES**

26, Shyam – 2 Industrial Hub, Nr. HOF, Moriya, Ahmedabad – 3822213 Call: - +91 9099051600, 9099139060, 7874379495

E-mail:- machinery.unitech@gmail.com