



- Vibro shifter work on gyro principle.
- The complete vibrating assembly is isolated from the base by means of specially designed rugged springs.
- Motor is fitted with top & bottom eccentric weights designed as per required centrifugal force.
- This whole assembly is covered by SS plate.
- The deck hopper is fabricated from SS 316L.
- The machine inner & outer surfaces are mirror polished.

SALIENT FEATURES:

- cGMP Model with contact part in SS 316, & Non-contact part in SS 304.
- Amplitude of Vibratory Motion adjustable through moveable eccentric weight.
- SS 316 Hood with dust free charging of powders.
- The machine can easily be dismantled, cleaned & assemble through quick opening SS 316 clamps.
- Finish: Inside - 0.3 Ra. Mirror polish.
Outside - 0.3 Ra. Mirror polish.
- Dust free docking station for loading and Unloading.
- Silicon Bonded integrated for all safety.

CAPACITY:

- 50 Kgs. – 2000 KGS per hour
- Mesh size (Inches):- 12,20,24,30,36,48,60,72,108

Manufactured & Exported By:

UNITECH MACHINERIES

26, Shyam - 2 Industrial Hub, Nr. HOF, Moriya, Ahmedabad - 3822213

Call: +91 9099051600, 9099139060, 7874379495.

E-mail: machinery.unitech@gmail.com